

FLD

INTELLOFAX 19

CLASSIFICATION ~~CONFIDENTIAL~~
 SECURITY INFORMATION
 CENTRAL INTELLIGENCE AGENCY

25X1A

959

INFORMATION REPORT

REPORT NO.

CD NO.

DATE DISTR. 16 November 1953

NO. OF PAGES 1

NO. OF ENCLS
(LISTED BELOW)SUPPLEMENT TO
REPORT NO.

COUNTRY Czechoslovakia
 SUBJECT 122 mm. Howitzer

PLACE
ACQUIREDDATE OF
INFO

25X1A

25X1X

The following are the specifications of the Czechoslovak howitzer 122:

1. Bore: 121.92 mm
2. Howitzer dimensions:
 - length 560 cm
 - breadth 180 cm
 - height 200 cm
 - weight 2300 kg
 - maximum speed 50 km/hr
3. Barrel:
 - length 280 cm
 - normal recoil 106 cm
 - max. recoil 110 cm
 - rifling dimensions 34 x 34
 - maximum elevation 50 degrees
 - breech is hand-operated
 - breechlock turns to right
 - firing mechanism lanyard-operated
4. Normal rate of fire: 6 rounds per minute
5. Order of fire controlled orally by battery commander, who has phone circuit to observer.

25X1A

